

Claims

1. (Original) An electromagnetic radiation detection system, comprising:

a body of SiC having a thickness of at least about 400 micrometers, and

5 a detector arranged to detect acoustic absorption of electromagnetic radiation having a wavelength less than about 10 micrometers by said SiC body.

2. (Original) The system of claim 1, wherein said detector is arranged to detect infrared (IR) radiation absorption by said SiC body.

3. (Original) The system of claim 1, wherein the thickness of said SiC body is in the approximate range of 400-2,000 micrometers.

4. (Original) The system of claim 1, wherein said detector is arranged to detect increases in the resistance of said SiC body in response to said body receiving radiation having a wavelength less than about 10 micrometers.

5. (Original) The system of claim 1, further comprising a filter arranged to limit the reception of radiation by said SiC body to a narrow wavelength band.

6. (Currently Amended) An electromagnetic radiation detection system of claim 1, comprising:

a body of SiC having a thickness of at least about 400 micrometers, wherein said SiC has a single crystal structure, and

a detector arranged to detect acoustic absorption of electromagnetic radiation having a wavelength less than about 10 micrometers by said SiC body.

7. (Previously Presented) The system of claim 1, wherein the thickness of said SiC body is uniform.

8. (Previously Presented) The system of claim 1, wherein said SiC body has a radiation receiving surface that is flat.

9. (Original) An electromagnetic radiation detection method, comprising:

irradiating a body of SiC having a thickness of at least about 400 micrometers with electromagnetic radiation having a wavelength less than about 10 micrometers, and

detecting an acoustic absorption response of said SiC body to said radiation.

10. (Original) The method of claim 9, wherein said SiC body is irradiated with infrared (IR) radiation.

11. (Original) The method of claim 9, wherein the thickness of said SiC body is in the approximate range of 400-2,000 micrometers.

12. (Original) The method of claim 9, wherein said acoustic absorption is detected by detecting increases in the resistance of said SiC body in response to said radiation.

13. (Original) The method of claim 9, wherein said radiation comprises a band of multiple wavelengths.

14. (Original) An electromagnetic radiation detection method, comprising:

irradiating a body of SiC having a thickness of at least about 400 micrometers with electromagnetic radiation having a wavelength less than about 10 micrometers, and

detecting a response of said SiC body to said radiation.

15. (Original) The method of claim 14, wherein said SiC body is irradiated with infrared (IR) radiation.

16. (Original) The method of claim 14, wherein the thickness of said SiC body is in the approximate range of 400-2,000 micrometers.

17. (Original) The method of claim 14, wherein said response is detected by detecting increases in the resistance of said SiC body in response to said radiation.

18. (Previously Presented) The method of claim 14, wherein said SiC body has uniform thickness.

19. (Previously Presented) An electromagnetic radiation detection method, comprising:

irradiating a uniform thickness body of SiC with radiation having a wavelength less than about 10 micrometers, and

detecting acoustic absorption of said radiation  
by said body.

20. (Original) The method of claim 19, wherein said  
SiC body is irradiated with infrared (IR) radiation.

21. (Original) The method of claim 19, wherein said  
acoustic absorption is detected by detecting increases in  
the resistance of said SiC body in response to said ra-  
diation.

22. (Previously Presented) An electromagnetic ra-  
diation detection method, comprising:

irradiating a body of SiC with radiation having  
a wavelength less than about 10 micrometers, said SiC  
5 body having a single crystal structure, and

detecting acoustic absorption of said radiation  
by said body.

23. (Original) The method of claim 22, wherein said  
SiC body is irradiated with infrared (IR) radiation.

24. (Original) The method of claim 23, wherein said  
acoustic absorption is detected by detecting increases in  
the resistance of said SiC body in response to said ra-  
diation.

25. (Original) The method of claim 22, wherein said  
acoustic absorption is detected over a band of multiple  
wavelengths.

Appl. No. 10/655,904  
Amdt. dated Jan. 9, 2006

26. (Original) The method of claim 22, further comprising filtering said radiation to a narrow wavelength band prior to irradiating said SiC body.